

RIG 67 - INTERNALLY GUYED SINGLE

Max Depth Capacity: 6,240'

Class II / III

MAST

Mast Type	<i>Stiff Single</i>	Drill Line Size	7/8"
Mast MFG	<i>CBI</i>	Number of Lines	4
Static Hook Load (lb)	<i>120,000</i>	3:1 Capacity (lb)	96,000
Mast Clear Height	<i>69'</i>	2:1 Capacity (lb)	145,000
Racking Cap. (4-1/2")	<i>2,880'</i>	Sandline Size	9/16" (6,560' Max)
Racking Cap. (3-1/2")	<i>4,080'</i>	Racking Cap. (2-7/8")	6,240'

Hoisting Service Line API Specification for EIPS 6 x 26 is:

3 : 1 Safety factor drilling; 2 : 1 Safety factor running, casing or stuck pipe.

INTERNAL GUYED COMPONENTS

Rig Beam MFG	<i>CBI</i>	Geronimo Plate MFG	<i>CBI</i>
Turnbuckles MFG	<i>CBI</i>		

CARRIER

Carrier MFG	<i>CBI</i>	Drawworks Drive	<i>MaxxForce 11</i>
Drawworks Model	<i>F.A.S.T. 450-LW</i>	Drive Rating (hp)	370
Rated Power (hp)	<i>450</i>	Transmission	<i>Allison 4500 RDS</i>
Main Drum Brake Size	<i>42" x 10"</i>	Sandline Brake	<i>Kobelc 5026 - 40" Disc</i>

OVERHEAD EQUIPMENT

Block Type	<i>McKissick 82-A</i>	Block Capacity (ton)	75
Bails Type	<i>Oil Country</i>	Bail Capacity (ton)	150
Rod Hook Type	<i>Trico Short Rod Hook</i>	Rod Hook Capacity (ton)	25
Tbg Elevator Type	<i>Gearench/Oil Country</i>	Tbg Elevator Size	2-3/8" to 3-1/2"
Rod Elevator Type	<i>Trico/O'Bannon</i>	Rod Elevator Size	5/8" to 1-1/8"

HANDLING EQUIPMENT

Tbg Tongs Type	<i>58-93R</i>	Tbg Tongs Size	2-3/8" to 4-1/2"
Rod Tongs Type	<i>Gill 300</i>	Rod Tongs Size	5/8" to 1-1/8"
Rod Backoff Tool Type	<i>Oil Country</i>	Rod Backoff Tool Size	3/4" to 1"

BOPs (NACE)

Annular MFG	<i>Control Technology</i>	Pressure Rating & Size	5,000 psi, 7-1/16"
Double Gate MFG	<i>Control Technology</i>	Pressure Rating & Size	5,000 psi, 7-1/16"
Kill Spool MFG	<i>Control Technology</i>	Pressure Rating & Size	5,000 psi, 2-1/16"
Safety Valve MFG	<i>Hi-Kalibre</i>	Pressure Rating & Size	5,000, 2-7/8" & 3-1/2"
Hydraulic Regan		Pressure Rating & Size	3,000 psi, 3" (Type - K)

ACCUMULATOR

Class II

Accumulator MFG	<i>Control Technology</i>	Max Operating Pressure (psi)	3,000
Accumulator Vol. (US gal)	20	# of Stations	2

ACCUMULATOR

Class III

Accumulator MFG	<i>Control Technology</i>	Max Operating Pressure (psi)	3,000
Accumulator Vol. (US gal)	40	# of Stations	3

SAFETY EQUIPMENT

Fire Extinguisher Size (qty)	30 lb (4)	Gas Detector	<i>Kitagawa</i>
SCBA Quantity	2 w/ Spare bottle	LEL Monitor	<i>Industrial Sc. 4-Gas</i>
Self Retracting Lifeline (qty)	2	Crown Saver	Yes
Tension Limiter	Yes	Pipe Ram Saver	Yes

MOBILE DOGHOUSE

Generator Sets	<i>Isuzu</i>	Prime Rating (hp)	53.6
Change Room Size	15' x 9'-4"	Bathroom Facilities	Yes
Generator House Size	15' x 9'-4"		

MOBILE PUMP & TANK

Truck MFG & Model	<i>Freightliner 2005</i>	Mud Pump Drive	<i>CAT C7</i>
Pump MFG & Model	<i>GD TEE 4 x 5</i>	Pump Drive Rating (hp)	300
Pump Rated Power (hp)	165	Pump Pressure (psi)	5,000
Pump Stroke Length	5"	Centrifugal Pump Size	4" x 3"
Manifold Valve Quantity	7	Transmission	<i>Allison 3000 RDS</i>
Manifold Rating (psi)	5,000	# of Tank Compartments	2
Total Tank Volume (bbl)	182	Line Pipe Rating (psi)	5,000

MISCELLANEOUS EQUIPMENT (OPTIONAL)

Low Lying Slips Type	<i>Mission</i>	Low Lying Slips Size	<i>As Required</i>
Personal H ₂ S Monitor	<i>As Required</i>	NORM Radiation Monitor	<i>As Required</i>
Catwalk	<i>As Required</i>	Pipe Racks	<i>As Required</i>
Drill Out Head	<i>As Required</i>	Mud Can	<i>As Required</i>
Skid Boiler (hp)	80		

Standard specifications represent the typical rig configuration, but could be subject to slight modifications from time to time due to customer requirements.