

# RIG 34 - INTERNALLY GUYED DOUBLE

Max Depth Capacity: 3,800 m

Class II

## MAST

Mast Type	<i>Telescopic Double</i>	Drill Line Size (mm)	25.4
Mast MFG	<i>CARE Industries</i>	Number of Lines	6
SHL - Externally Guyed (daN)	<i>89,000</i>	3:1 Capacity (daN)	<i>80,300</i>
SHL - Free Standing (daN)	<i>80,000</i>	2:1 Capacity (daN)	<i>120,400</i>
Mast Clear Height (m)	<i>32.0</i>	Sandline Size (mm)	<i>12.7 (4,200 m Max)</i>
Racking Cap. -88.9mm (m)	<i>3,800</i>		

**Hoisting Service Line API Specification for EIPS 6 x 26 is:**

**3 : 1 Safety factor hoisting; 2 : 1 Safety factor pulling on stuck pipe and similar infrequent operations.**

## INTERNAL GUYED COMPONENTS

Rig Beam MFG	<i>CARE Industries</i>	Geronimo Plate MFG	<i>CARE Industries</i>
Turnbuckles MFG	<i>CARE Industries</i>		

## CARRIER

Carrier MFG	<i>CARE Industries</i>	Drawworks Drive	<i>CAT C11</i>
Drawworks Model	<i>ALCO 42X10</i>	Drive Rating (kW)	<i>287</i>
Rated Power (kW)	<i>336</i>	Transmission	<i>Allison OFS 4700</i>
Main Drum Brake Size (mm)	<i>1,067 x 254</i>	Sandline Drum Brake Size (mm)	<i>965 x 203</i>
Auxiliary Brake	<i>Kobel 1,016 mm Disc</i>		

## OVERHEAD EQUIPMENT

Block Type	<i>Oil Country 100T</i>	Block Capacity (daN)	<i>89,000</i>
Bails Type	<i>Oil Country 150T</i>	Bail Capacity (daN)	<i>133,400</i>
Rod Hook Type	<i>Oil Country RH-35</i>	Rod Hook Capacity (daN)	<i>31,100</i>
Tbg Elevator Type	<i>Oil Country / AOT</i>	Tbg Elevator Size (mm)	<i>60.3 to 114.3</i>
Rod Elevator Type	<i>Oil Country Plate Type</i>	Rod Elevator Size (mm)	<i>15.8 To 25.4</i>

## HANDLING EQUIPMENT

Tbg Tongs Type	<i>Oil Country 58-93</i>	Tbg Tongs Size (mm)	<i>60.3 to 88.9</i>
Air Slips Type	<i>C</i>		

## BOPs (NACE)

Double Gate MFG	<i>HRSB</i>	Pressure Rating & Size	<i>34,500 kPa, 179 mm</i>
Kill Spool Pressure Rating & Size			<i>34,500 kPa, 179 mm c/w 50.8 mm Outlet and Valve</i>
Safety Valve Pressure Rating & Size			<i>34,500 kPa, 73 mm</i>
Hydraulic Regan Pressure Rating & Size			<i>21,000 kPa, 76.2 mm (Type - K)</i>

## ACCUMULATOR

<b>Class II</b>			
Accumulator MFG	<i>Control Technology</i>	Max Operating Pressure (kPa)	<i>21,000</i>
Accumulator Vol. (l)	<i>76</i>	# of Stations	<i>2</i>

### SAFETY EQUIPMENT

Fire Extinguisher Size (qty)	13.6 kg (4)	Gas Detector	Yes
SCBA Quantity	2 w/ Spare Bottle	LEL Monitor	Yes
Self Retracting Lifeline (qty)	2	Crown Saver	Yes
		Pipe Ram Saver	Yes

### MOBILE DOGHOUSE

Generator Sets	Isuzu	Prime Rating (kW)	40
Change Room Size (m)	4.26 x 2.85	Bathroom Facilities	Yes
Generator House Size (m)	4.57 x 2.85	Wi-Fi Hotspot Booster	Yes

### MOBILE PUMP & TANK (OPTIONAL EQUIPMENT)

Truck MFG & Model	Freightliner 2009	Mud Pump Drive	Mercedes MBE 4000
Pump MFG & Model	SJ Petro 300	Pump Drive Rating (kW)	261
Pump Rated Power (kW)	261	Pump Pressure (kPa)	34,500
Pump Stroke Length (mm)	127	Bowie Pump Size (mm)	101.6
Manifold Valve Quantity	7	Transmission	Allison 4500 RDS
Manifold Rating (kPa)	34,500	# of Tank Compartments	2
Total Tank Volume (m <sup>3</sup> )	34	Line Pipe Rating (kPa)	34,500

### MISCELLANEOUS EQUIPMENT (OPTIONAL)

Rod Tongs Type	M50	Rod Tongs Size (mm)	As Required
Rod Backoff Tool Type	Oil Country	Rod Backoff Tool Size (mm)	As Required
Low Lying Slips Type	Bosch	Low Lying Slips Size (mm)	As Required
Personal H <sub>2</sub> S Monitor	As Required	NORM Radiation Monitor	As Required
Drill Out Head (mm)	As Required	Pipe Trailer	As Required
Skid Boiler (kW)	60	Mud Can	As Required

*Standard specifications represent the typical rig configuration, but could be subject to slight modifications from time to time due to customer requirements.*