



# RIG 68 - INTERNALLY GUYED SINGLE

Max Depth Capacity: 6,240'

CARB Compliant On-Highway

## MAST

Mast Type	<i>Stiff Single</i>	Drill Line Size	<i>7/8"</i>
Mast MFG	<i>CBI</i>	Number of Lines	<i>4</i>
Static Hook Load (lb)	<i>120,000</i>	3:1 Capacity (lb)	<i>96,000</i>
Mast Clear Height	<i>69'</i>	2:1 Capacity (lb)	<i>145,000</i>
Racking Cap. (4-1/2")	<i>2,880'</i>	Sandline Size	<i>9/16" (6,560' Max)</i>
Racking Cap. (3-1/2")	<i>4,080'</i>	Racking Cap. (2-7/8")	<i>6,240'</i>

**Drill Line API Specification for EIPS 6 x 26 is:**

**3 : 1 Safety factor drilling; 2 : 1 Safety factor running, casing or stuck pipe.**

## INTERNAL GUYED COMPONENTS

Rig Beam MFG	<i>CBI</i>	Turnbuckles MFG	<i>CBI</i>
--------------	------------	-----------------	------------

## CARRIER

Carrier MFG	<i>CBI</i>	Drawworks Drive	<i>MaxxForce 11</i>
Drawworks Model	<i>F.A.S.T. 450-LW</i>	Drive Rating (hp)	<i>370</i>
Rated Power (hp)	<i>450</i>	Transmission	<i>Allison 4500 RDS</i>
Main Drum Brake Size	<i>42" x 10"</i>	Sandline Brake	<i>Kobelt 5026 - 40" Disc</i>

## OVERHEAD EQUIPMENT

Block Type	<i>McKissick 82-A</i>	Block Capacity (ton)	<i>75</i>
Bails Type	<i>King Oil Tools</i>	Bail Capacity (ton)	<i>150</i>
Rod Hook Type	<i>Trico Short Rod Hook</i>	Rod Hook Capacity (ton)	<i>25</i>
Tbg Elevator Type	<i>Gearench</i>	Tbg Elevator Size	<i>2-7/8" to 3-1/2"</i>
Rod Elevator Type	<i>Trico</i>	Rod Elevator Size	<i>5/8" to 1-1/8"</i>

## HANDLING EQUIPMENT

Tbg Tongs Type	<i>Open Face</i>	Tbg Tongs Size	<i>2-3/8" to 3-1/2"</i>
Rod Tongs Type	<i>Gill 300</i>	Rod Tongs Size	<i>5/8" to 1-1/8"</i>
Rod Backoff Tool Type	<i>Oil Country</i>	Rod Backoff Tool Size	<i>3/4" to 1"</i>

## BOPs (NACE)

Double Gate MFG	<i>Boss</i>	Pressure Rating & Size	<i>5,000 psi, 7-1/16"</i>
Kill Spool MFG	<i>ACD</i>	Pressure Rating & Size	<i>5,000 psi, 2-1/16"</i>
Safety Valve MFG	<i>Hi-Kalibre</i>	Pressure Rating & Size	<i>5,000, 2-7/8" &amp; 3-1/2"</i>
Hydraulic Regan Pressure Rating & Size			<i>3,000 psi, 3" (Type - K)</i>

## ACCUMULATOR

Accumulator MFG	<i>Control Technology</i>	Max Operating Pressure (psi)	<i>3,000</i>
Accumulator Vol. (US gal)	<i>20</i>	# of Stations	<i>2</i>

## SAFETY EQUIPMENT

Fire Extinguisher Size (qty)	<i>30 lb (2)</i>	Gas Detector	<i>Kitagawa</i>
Self Retracting Lifeline (qty)	<i>2</i>	Crown Saver	<i>Yes</i>
LEL Monitor	<i>Industrial Sc. 4-Gas</i>	Pipe Ram Saver	<i>Yes</i>

## Sales and Marketing

Western Oilfield Services

Tel: 1-661-477-5899 Email: [sales@wofservices.com](mailto:sales@wofservices.com)

Standard specifications represent the typical rig configuration, but could be subject to slight modifications from time to time due to customer requirements.