



RIG 60 - INTERNALLY GUYED SINGLE

Max Depth Capacity: 6,240'

CARB Compliant On-Highway

MAST

Mast Type	<i>Stiff Single</i>	Drill Line Size	7/8"
Mast MFG	<i>CBI</i>	Number of Lines	4
Static Hook Load (lb)	<i>120,000</i>	3:1 Capacity (lb)	96,000
Mast Clear Height	<i>69'</i>	2:1 Capacity (lb)	145,000
Racking Cap. (4-1/2")	<i>2,880'</i>	Sandline Size	9/16" (6,560' Max)
Racking Cap. (3-1/2")	<i>4,080'</i>	Racking Cap. (2-7/8")	6,240'

Hoisting Service Line API Specification for EIPS 6 x 26 is:

3 : 1 Safety factor hoisting; 2 : 1 Safety factor pulling on stuck pipe and similar infrequent operations.

INTERNAL GUYED COMPONENTS

Rig Beam MFG	<i>CBI</i>	Turnbuckles MFG	<i>CBI</i>
--------------	------------	-----------------	------------

CARRIER

Carrier MFG	<i>CBI</i>	Drawworks Drive	<i>MaxxForce 11</i>
Drawworks Model	<i>F.A.S.T. 450-LW</i>	Drive Rating (hp)	370
Rated Power (hp)	<i>450</i>	Transmission	<i>Allison 4500 RDS</i>
Main Drum Brake Size	<i>42" x 10"</i>	Sandline Brake	<i>Kobelco 5026 - 40" Disc</i>

OVERHEAD EQUIPMENT

Block Type	<i>McKissick 82-A</i>	Block Capacity (ton)	75
Bails Type	<i>King Oil Tools</i>	Bail Capacity (ton)	150
Rod Hook Type	<i>Trico Short Rod Hook</i>	Rod Hook Capacity (ton)	25
Tbg Elevator Type	<i>Gearench</i>	Tbg Elevator Size	2-7/8" to 3-1/2"
Rod Elevator Type	<i>Trico</i>	Rod Elevator Size	5/8" to 1-1/8"

HANDLING EQUIPMENT

Tbg Tongs Type	<i>Open Face</i>	Tbg Tongs Size	2-3/8" to 3-1/2"
Rod Tongs Type	<i>Gill 300</i>	Rod Tongs Size	5/8" to 1-1/8"
Rod Backoff Tool Type	<i>Oil Country</i>	Rod Backoff Tool Size	3/4" to 1"

BOPs (NACE)

Double Gate MFG	<i>Boss</i>	Pressure Rating & Size	5,000 psi, 7-1/16"
Kill Spool MFG	<i>ACD</i>	Pressure Rating & Size	5,000 psi, 2-1/16"
Safety Valve MFG	<i>Hi-Kalibre</i>	Pressure Rating & Size	5,000, 2-7/8" & 3-1/2"
Hydraulic Regan Pressure Rating & Size			3,000 psi, 3" (Type - K)

ACCUMULATOR

Accumulator MFG	<i>Control Technology</i>	Max Operating Pressure (psi)	3,000
Accumulator Vol. (US gal)	<i>20</i>	# of Stations	2

SAFETY EQUIPMENT

Fire Extinguisher Size (qty)	<i>30 lb (2)</i>	Gas Detector	<i>Kitagawa</i>
Self Retracting Lifeline (qty)	<i>2</i>	Crown Saver	Yes
LEL Monitor	<i>Industrial Sc. 4-Gas</i>	Pipe Ram Saver	Yes

Sales and Marketing

Western Oilfield Services

Tel: 1-661-477-5899 Email: sales@wofservices.com

Standard specifications represent the typical rig configuration, but could be subject to slight modifications from time to time due to customer requirements.