



**MAST**

Mast Type	<i>Slant</i>	Drill Line Size (mm)	22.2
Mast MFG	<i>CARE Industries</i>	Number of Lines	4
SHL - Vertical (daN)	<i>55,600</i>	3:1 Capacity (daN)	<i>42,900</i>
SHL - Slant (daN)	<i>48,900</i>	2:1 Capacity (daN)	<i>64,400</i>
Mast Clear Height (m)	<i>21.3</i>	Racking Cap.-60.3mm (m)	<i>2,600</i>

**Drill Line API Specification for EIPS 6 x 26 is:**

**3 : 1 Safety factor hoisting; 2 : 1 Safety factor pulling on stuck pipe and similar infrequent operations.**

**FREE STANDING COMPONENTS**

H Base MFG	<i>CARE Industries</i>	Geronimo Plate MFG	<i>CARE Industries</i>
Load Beam MFG	<i>CARE Industries</i>	Trunnion Arm MFG	<i>CARE Industries</i>

**CARRIER**

Carrier MFG	<i>CARE Industries</i>	Drawworks Drive	<i>CAT C11</i>
Drawworks Model	<i>Hulkster 400-D</i>	Drive Rating (kW)	<i>287</i>
Rated Power (kW)	<i>261</i>	Transmission	<i>Allison OFS 4700</i>
Main Drum Brake Size (mm)	<i>965 x 203</i>	Pull Down Winch Capacity (daN)	<i>15,600</i>

**OVERHEAD EQUIPMENT**

Block Type	<i>Skytop 75T</i>	Block Capacity (daN)	<i>66,700</i>
Bails Type	<i>Adams Steel 75T</i>	Bail Capacity (daN)	<i>66,700</i>
Rod Hook Type	<i>Trico 17.5T</i>	Rod Hook Capacity (daN)	<i>15,600</i>
Tbg Elevator Type	<i>Option Industries</i>	Tbg Elevator Size (mm)	<i>60.3 to 88.9</i>
Rod Elevator Type	<i>Trico Plate Type</i>	Rod Elevator Size (mm)	<i>15.9 To 28.6</i>

**HANDLING EQUIPMENT**

Tbg Tongs Type	<i>Oil Country CH-58</i>	Tbg Tongs Size (mm)	<i>60.3 to 114.3</i>
Rod Tongs Type	<i>Gill 300</i>	Rod Tongs Size (mm)	<i>19.1 to 25.4</i>
Tbg Rotator Type	<i>Option Industries</i>	Tbg Rotator Size (mm)	<i>60.3 to 88.9</i>
X-Celerator Type	<i>C-Tech X-250</i>	X-Celerator Capacity (daN)	<i>11,100</i>
Air Slips Type	<i>C</i>	Power Swivel Cart Cap. (daN)	<i>40,000 to 75,600</i>

**BOPs (NACE)**

Double Gate MFG	<i>Boss</i>	Pressure Rating & Size	<i>34,500 kPa, 179 mm</i>
Kill Spool Pressure Rating & Size			<i>21,000 kPa, 179 mm c/w 50.8 mm Outlet and Valve</i>
Safety Valve Pressure Rating & Size			<i>34,500 kPa, 73.0 mm &amp; 88.9 mm</i>
Hydraulic Regan Pressure Rating & Size			<i>21,000 kPa, 76.2 mm (Type - K)</i>

**ACCUMULATOR**

**Class II**

Accumulator MFG	<i>Control Technology</i>	Max Operating Pressure (kPa)	<i>21,000</i>
Accumulator Vol. (l)	<i>76</i>	# of Stations	<i>2</i>

### SAFETY EQUIPMENT

Fire Extinguisher Size (qty)	13.6 kg (4)	Gas Detector	Yes
SCBA Quantity	2 w/ Spare Bottle	LEL Monitor	Yes
Self Retracting Lifeline (qty)	2	Crown Saver	Yes
		Pipe Ram Saver	Yes

### MOBILE DOGHOUSE

Generator Sets	Yanmar	Prime Rating (kW)	40
Change Room Size (m)	4.57 x 2.85	Bathroom Facilities	Yes
Generator House Size (m)	4.57 x 2.85	Wi-Fi Hotspot Booster	Yes

### EQUIPMENT TRUCK WITH PICKER

Crane MFG & Model	Amco Veba V820	Crane Lifting Capacity (kg)	4,171
Truck MFG & Model	Freightliner M2		

### MOBILE PUMP & TANK (OPTIONAL EQUIPMENT)

Truck MFG & Model	International 2015	Mud Pump Drive	Navistar N13
Pump MFG & Model	GD TEE 4 x 5	Pump Drive Rating (kW)	306
Pump Rated Power (kW)	123	Pump Pressure (kPa)	34,500
Pump Stroke Length (mm)	127	Centrifugal Pump Size (mm)	101 x 76
Manifold Valve Quantity	7	Transmission	Allison 4500 OFS
Manifold Rating (kPa)	35,000	# of Tank Compartments	2
Total Tank Volume (m <sup>3</sup> )	32	Line Pipe Rating (kPa)	34,500

### MISCELLANEOUS EQUIPMENT (OPTIONAL)

Rod Tongs Type	M50	Rod Tongs Size (mm)	As Required
Rod Backoff Tool Type	Oil Country	Rod Backoff Tool Size (mm)	As Required
Low Lying Slips Type	Bosch	Low Lying Slips Size (mm)	As Required
Personal H <sub>2</sub> S Monitor	As Required	NORM Radiation Monitor	As Required
Drill Out Head (mm)	As Required	Pipe Trailer	As Required
Skid Boiler (kW)	60	Mud Can	As Required

*Standard specifications represent the typical rig configuration, but could be subject to slight modifications from time to time due to customer requirements.*