

RIG 63 - INTERNALLY GUYED SINGLE

Max Depth Capacity: 6,240'

Class II

MAST

| | | | |
|-----------------------|---------------------|-----------------------|---------------------------|
| Mast Type | <i>Stiff Single</i> | Drill Line Size | 1" |
| Mast MFG | <i>CBI</i> | Number of Lines | 4 |
| Static Hook Load (lb) | <i>120,000</i> | 3:1 Capacity (lb) | <i>125,000</i> |
| Mast Clear Height | <i>69'</i> | 2:1 Capacity (lb) | <i>188,000</i> |
| Racking Cap. (4-1/2") | <i>2,880'</i> | Sandline Size | <i>9/16" (9,840' Max)</i> |
| Racking Cap. (3-1/2") | <i>4,080'</i> | Racking Cap. (2-7/8") | <i>6,240'</i> |

Drill Line API Specification for EIPS 6 x 26 is:

3 : 1 Safety factor drilling; 2 : 1 Safety factor running, casing or stuck pipe.

INTERNAL GUYED COMPONENTS

| | | | |
|-----------------|------------|--------------------|------------|
| Rig Beam MFG | <i>CBI</i> | Geronimo Plate MFG | <i>CBI</i> |
| Turnbuckles MFG | <i>CBI</i> | | |

CARRIER

| | | | |
|----------------------|---------------------|-------------------|-------------------------------|
| Carrier MFG | <i>CBI</i> | Drawworks Drive | <i>MaxxForce 11</i> |
| Drawworks Model | <i>F.A.S.T. 450</i> | Drive Rating (hp) | <i>370</i> |
| Rated Power (hp) | <i>450</i> | Transmission | <i>Allison 4500 RDS</i> |
| Main Drum Brake Size | <i>42" x 10"</i> | Sandline Brake | <i>Kobelc 5026 - 40" Disc</i> |

OVERHEAD EQUIPMENT

| | | | |
|-------------------|-----------------------------|-------------------------|-------------------------|
| Block Type | <i>McKissick 82-A</i> | Block Capacity (ton) | <i>75</i> |
| Bails Type | <i>King Oil Tools</i> | Bail Capacity (ton) | <i>150</i> |
| Rod Hook Type | <i>Trico Short Rod Hook</i> | Rod Hook Capacity (ton) | <i>25</i> |
| Tbg Elevator Type | <i>Gearench</i> | Tbg Elevator Size | <i>2-3/8" to 3-1/2"</i> |
| Rod Elevator Type | <i>Trico</i> | Rod Elevator Size | <i>5/8" to 1-1/8"</i> |

HANDLING EQUIPMENT

| | | | |
|-----------------------|---------------------|---------------------------|-------------------------|
| Tbg Tongs Type | <i>58-93R</i> | Tbg Tongs Size | <i>2-3/8" to 4-1/2"</i> |
| Rod Tongs Type | <i>M50</i> | Rod Tongs Size | <i>5/8" to 1-1/8"</i> |
| Rod Backoff Tool Type | <i>Oil Country</i> | Rod Backoff Tool Size | <i>3/4" to 1"</i> |
| X-Celerator Type | <i>C-Tech X-250</i> | X-Celerator Capacity (lb) | <i>25,000</i> |

BOPs (NACE)

| | | | |
|--|-------------------|------------------------|-----------------------------------|
| Double Gate MFG | <i>Boss</i> | Pressure Rating & Size | <i>5,000 psi, 7-1/16"</i> |
| Kill Spool MFG | <i>ACD</i> | Pressure Rating & Size | <i>5,000 psi, 2-1/16"</i> |
| Safety Valve MFG | <i>Hi-Kalibre</i> | Pressure Rating & Size | <i>5,000, 2-7/8" & 3-1/2"</i> |
| Hydraulic Regan Pressure Rating & Size | | | <i>3,000 psi, 3" (Type - K)</i> |

ACCUMULATOR

| | | | |
|---------------------------|---------------------------|------------------------------|--------------|
| Class II | | | |
| Accumulator MFG | <i>Control Technology</i> | Max Operating Pressure (psi) | <i>3,000</i> |
| Accumulator Vol. (US gal) | <i>20</i> | # of Stations | <i>2</i> |



Sales and Marketing
Eagle Well Servicing
Tel: 1-877-346-9710 Email: sales@eaglerigs.com

SAFETY EQUIPMENT

| | | | |
|--------------------------------|-------------------|----------------|----------------------|
| Fire Extinguisher Size (qty) | 30 lb (4) | Gas Detector | Kitagawa |
| SCBA Quantity | 2 w/ Spare bottle | LEL Monitor | Industrial Sc. 4-Gas |
| Self Retracting Lifeline (qty) | 2 | Crown Saver | Yes |
| | | Pipe Ram Saver | Yes |

MOBILE DOGHOUSE

| | | | |
|----------------------|-------------|-----------------------|------|
| Generator Sets | Yanmar | Prime Rating (hp) | 53.6 |
| Change Room Size | 15' x 9'-8" | Bathroom Facilities | Yes |
| Generator House Size | 15' x 9'-8" | Wi-Fi Hotspot Booster | Yes |

EQUIPMENT TRUCK WITH PICKER

| | | | |
|-------------------|-----------------|-----------------------------|--------|
| Crane MFG & Model | Hiab 200C | Crane Lifting Capacity (lb) | 11,023 |
| Truck MFG & Model | Freightliner M2 | | |

MISCELLANEOUS EQUIPMENT (OPTIONAL)

| | | | |
|-----------------------------------|------------------|------------------------|-------------|
| Low Lying Slips Type | Boscher Holdings | Low Lying Slips Size | As Required |
| Personal H ₂ S Monitor | As Required | NORM Radiation Monitor | As Required |
| Drill Out Head | As Required | Pipe Trailer | As Required |
| Mobile Pump & Tank | As Required | Skid Boiler (hp) | As Required |
| Mud Can | As Required | | |

Standard specifications represent the typical rig configuration, but could be subject to slight modifications from time to time due to customer requirements.