



MAST

Mast Type	<i>Telescopic Double</i>	Drill Line Size (mm)	25.4
Mast MFG	<i>CARE Industries</i>	Number of Lines	8
SHL - Externally Guyed (daN)	111,200	3:1 Capacity (daN)	103,600
SHL - Free Standing (daN)	89,000	2:1 Capacity (daN)	155,400
Mast Clear Height (m)	32.0	Sandline Size (mm)	12.7 (4,200 m Max)
Racking Cap.-88.9mm (m)	4,200		

Drill Line API Specification for EIPS 6 x 26 is:

3 : 1 Safety factor drilling; 2 : 1 Safety factor running casing or stuck pipe.

INTERNAL GUYED COMPONENTS

Rig Beam MFG	<i>CARE Industries</i>	Geronimo Plate MFG	<i>CARE Industries</i>
Turnbuckles MFG	<i>CARE Industries</i>	T-Sill & Ramp MFG	<i>CARE Industries</i>

CARRIER

Carrier MFG	<i>CARE Industries</i>	Drawworks Drive	<i>CAT C15</i>
Drawworks Model	<i>ALCO 42X10</i>	Drive Rating (kW)	403
Rated Power (kW)	410	Transmission	<i>Allison OFS 4700</i>
Main Drum Brake Size (mm)	1,067 x 254	Sandline Drum Brake Size (mm)	965 x 203
Auxiliary Brake	<i>Kobelt 1,219 mm Disc</i>		

OVERHEAD EQUIPMENT

Block Type	<i>Oil Country 100T</i>	Block Capacity (daN)	89,000
Bails Type	<i>King Oil Tools 250T</i>	Bail Capacity (daN)	222,000
Rod Hook Type	<i>Trico 25T</i>	Rod Hook Capacity (daN)	22,200
Tbg Elevator Type	<i>Gearench / AOT</i>	Tbg Elevator Size (mm)	60.3 to 88.9
Rod Elevator Type	<i>Trico Plate Type</i>	Rod Elevator Size (mm)	19.1 To 25.4

HANDLING EQUIPMENT

Tbg Tongs Type	<i>McCoy</i>	Tbg Tongs Size (mm)	30.1 to 127.0
Air Slips Type	C		

BOPs (NACE)

Annular MFG	<i>Townsend</i>	Pressure Rating & Size	21,000 kPa, 346 mm
Double Gate MFG	<i>Townsend</i>	Pressure Rating & Size	21,000 kPa, 346 mm
Kill Spool Pressure Rating & Size			34,500 kPa, 179 mm c/w 50.8 mm Outlet and Valve
Safety Valve Pressure Rating & Size			34,500 kPa, 73.0 mm & 88.9 mm
Hydraulic Regan Pressure Rating & Size			21,000 kPa, 76.2mm (Type - K)

ACCUMULATOR

Class III			
Accumulator MFG	<i>Control Technology</i>	Max Operating Pressure (kPa)	21,000
Accumulator Vol. (l)	757	# of Stations	3
Shear Ram Booster	Yes		

SAFETY EQUIPMENT

Fire Extinguisher Size (qty)	13.6 kg (4)	Gas Detector	Yes
SCBA Quantity	2 w/ Spare Bottle	LEL Monitor	Yes
Self Retracting Lifeline (qty)	2	Crown Saver	Yes
		Pipe Ram Saver	Yes

MOBILE DOGHOUSE

Generator Sets	Isuzu	Prime Rating (kW)	60
Change Room Size (m)	4.57 x 2.85	Bathroom Facilities	Yes
Generator House Size (m)	4.57 x 2.85		
Torque/Turn System	McCoy WINCATT		

MOBILE PUMP & TANK (OPTIONAL EQUIPMENT)

Truck MFG & Model	Freightliner 2013	Mud Pump Drive	Detroit DD13
Pump MFG & Model	SJ Petro 300	Pump Drive Rating (kW)	306
Pump Rated Power (kW)	261	Pump Pressure (kPa)	34,500
Pump Stroke Length (mm)	127	Bowie Pump Size (mm)	101.6
Manifold Valve Quantity	7	Transmission	Allison 4500 RDS
Manifold Rating (kPa)	34,500	# of Tank Compartments	2
Total Tank Volume (m ³)	32	Line Pipe Rating (kPa)	34,500

MISCELLANEOUS EQUIPMENT (OPTIONAL)

Rod Tongs Type	M50	Rod Tongs Size (mm)	As Required
Rod Backoff Tool Type	Oil Country	Rod Backoff Tool Size (mm)	As Required
Low Lying Slips Type	Bosch	Low Lying Slips Size (mm)	As Required
Personal H ₂ S Monitor	As Required	NORM Radiation Monitor	As Required
Drill Out Head (mm)	As Required	Mud Can	As Required
Skid Boiler (kW)	60	Catwalk	Smart Iron RIII

Standard specifications represent the typical rig configuration, but could be subject to slight modifications from time to time due to customer requirements.