



MAST

Mast Type	<i>Telescopic Double</i>	Drill Line Size (in)	1
Mast MFG	<i>CARE Industries</i>	Number of Lines	8
SHL - Externally Guyed (lb)	<i>250,000</i>	3:1 Capacity (lb)	<i>232,900</i>
SHL - Free Standing (lb)	<i>200,000</i>	2:1 Capacity (lb)	<i>349,350</i>
Mast Clear Height (ft)	<i>105</i>	Sandline Size	<i>1/2" (13,780' Max)</i>
Racking Cap. (3-1/2")	<i>13,780</i>		

Drill Line API Specification for EIPS 6 x 26 is:

3 : 1 Safety factor drilling; 2 : 1 Safety factor running casing or stuck pipe.

INTERNAL GUYED COMPONENTS

Rig Beam MFG	<i>CARE Industries</i>	Geronimo Plate MFG	<i>CARE Industries</i>
Turnbuckles MFG	<i>CARE Industries</i>	T-Sill & Ramp MFG	<i>CARE Industries</i>

CARRIER

Carrier MFG	<i>CARE Industries</i>	Drawworks Drive	<i>CAT C15</i>
Drawworks Model	<i>ALCO 42X10</i>	Drive Rating (hp)	<i>540</i>
Rated Power (hp)	<i>550</i>	Transmission	<i>Allison OFS 4700</i>
Main Drum Brake Size (in)	<i>42 x 10</i>	Sandline Drum Brake Size	<i>38" x 8"</i>
Auxiliary Brake	<i>Kobelt 48" Disc</i>		

OVERHEAD EQUIPMENT

Block Type	<i>Oil Country 100T</i>	Block Capacity (ton)	<i>100</i>
Bails Type	<i>King Oil Tools 250T</i>	Bail Capacity (ton)	<i>250</i>
Rod Hook Type	<i>Trico 25T</i>	Rod Hook Capacity (ton)	<i>25</i>
Tbg Elevator Type	<i>Gearench / AOT</i>	Tbg Elevator Size	<i>2-3/8" to 3-1/2"</i>
Rod Elevator Type	<i>Trico Plate Type</i>	Rod Elevator Size	<i>3/4" to 1"</i>

HANDLING EQUIPMENT

Tbg Tongs Type	<i>McCoy</i>	Tbg Tongs Size	<i>1-3/16" to 5"</i>
Air Slips Type	<i>C</i>		

BOPs (NACE)

Annular MFG	<i>Townsend</i>	Pressure Rating & Size	<i>3,000 psi, 13-5/8"</i>
Double Gate MFG	<i>Townsend</i>	Pressure Rating & Size	<i>3,000 psi, 13-5/8"</i>
Kill Spool Pressure Rating & Size			<i>5,000 psi, 7-1/16" c/w 2" Outlet and Valve</i>
Safety Valve Pressure Rating & Size			<i>5,000 psi, 2-7/8" & 3-1/2"</i>
Hydraulic Regan Pressure Rating & Size			<i>3,000 psi, 3" (Type - K)</i>

ACCUMULATOR

Class III			
Accumulator MFG	<i>Control Technology</i>	Max Operating Pressure (psi)	<i>3,000</i>
Accumulator Vol. (US gal)	<i>200</i>	# of Stations	<i>3</i>
Shear Ram Booster	<i>Yes</i>		

SAFETY EQUIPMENT

Fire Extinguisher Size (qty)	30 lb (4)	Gas Detector	Yes
SCBA Quantity	2 w/ Spare Bottle	LEL Monitor	Yes
Self Retracting Lifeline (qty)	2	Crown Saver	Yes
		Pipe Ram Saver	Yes

MOBILE DOGHOUSE

Generator Sets	Isuzu	Prime Rating (hp)	80
Change Room Size	15' x 9'-4"	Bathroom Facilities	Yes
Generator House Size	15' x 9'-4"		
Torque/Turn System	McCoy WINCATT		

MOBILE PUMP & TANK (OPTIONAL EQUIPMENT)

Truck MFG & Model	Freightliner 2013	Mud Pump Drive	Detroit DD13
Pump MFG & Model	SJ Petro 300	Pump Drive Rating (hp)	410
Pump Rated Power (hp)	350	Pump Pressure (psi)	5,000
Pump Stroke Length	5"	Bowie Pump Size	4"
Manifold Valve Quantity	7	Transmission	Allison 4500 RDS
Manifold Rating (psi)	5,000	# of Tank Compartments	2
Total Tank Volume (bbl)	200	Line Pipe Rating (psi)	5,000

MISCELLANEOUS EQUIPMENT (OPTIONAL)

Rod Tongs Type	M50	Rod Tongs Size	As Required
Rod Backoff Tool Type	Oil Country	Rod Backoff Tool Size	As Required
Low Lying Slips Type	Bosch	Low Lying Slips Size	As Required
Personal H ₂ S Monitor	As Required	NORM Radiation Monitor	As Required
Drill Out Head	As Required	Mud Can	As Required
Skid Boiler (hp)	80	Catwalk	Smart Iron RIII

Standard specifications represent the typical rig configuration, but could be subject to slight modifications from time to time due to customer requirements.