

# **AGLE** RIG 2 - INTERNALLY GUYED SINGLE

Max Depth Capacity: 9,150'

Class II

9.150'

# MAST

M A Western Co.

Mast Type	Stiff Single	Drill Line Size	1"	
Mast MFG	BW Rig	Number of Lines	4	

 Static Hook Load (lb)
 140,000
 3:1 Capacity (lb)
 125,000

 Mast Clear Height
 70'
 2:1 Capacity (lb)
 188,000

Racking Cap. (3-1/2") 6,890' Sandline Size 9/16" (9,840' Max)

Racking Cap. (2-7/8") 8,200' Racking Cap. (2-3/8")

**Drill Line API Specification for EIPS 6 x 26 is:** 

3: 1 Safety factor drilling; 2: 1 Safety factor running casing or stuck pipe.

#### INTERNAL GUYED COMPONENTS

Rig Beam MFG Mainland Geronimo Plate MFG BW Rig

Outriggers MFG BW Rig

### **CARRIER**

Carrier MFG	Mainland	Drawworks Drive	CAT 11
Drawworks Model	Mainland M40	Drive Rating (hp)	325

Rated Power (hp) 400 Transmission Allison 750
Main Drum Brake Size 40" x 10" Sandline Drum Brake Size 40" x 10"

#### **OVERHEAD EQUIPMENT**

Block Type McKissick 75T Block Capacity (ton) 75
Bails Type Tool Pusher 150T Bail Capacity (ton) 125
Rod Hook Type Trico 25T Rod Hook Capacity (ton) 25

Tbg Elevator Type Diehl / Gearench / AOT Tbg Elevator Size 2-3/8" to 3-1/2"
Rod Elevator Type O'Bannon / Trico / Neilson Rod Elevator Size 5/8" to 1"

### HANDLING EQUIPMENT

Tbg Tongs TypeGill 58-93Tbg Tongs Size2-3/8" to 3-1/2"Rod Tongs TypeOil Country Mark 4Rod Tongs Size3/4" to 1"Rod Backoff Tool TypeOil CountryRod Backoff Tool Size3/4" to 1"

Air Slips Type C

#### **BOPs (NACE)**

Double Gate MFG WSI Duke Pressure Rating & Size 3,000 psi, 7-1/16"

Kill Spool Pressure Rating & Size 3,000 psi, 7-1/16" c/w 2" Outlet and Valve

Safety Valve Pressure Rating & Size 5,000 psi, 2-7/8"

Hydraulic Regan Pressure Rating & Size 3,000 psi, 3" (Type - K)

#### **ACCUMULATOR**

#### Class II

Accumulator MFG Control Technology Max Operating Pressure (psi) 3,000
Accumulator Vol. (US gal) 20 # of Stations 2



AGLE Sales and Marketing **Eagle Well Servicing** 

Tel: 1-877-346-9710 📉 A Western Co.

Email: sales@eaglerigs.com

## **SAFETY EQUIPMENT**

Fire Extinguisher Size (qty)	30 lb (4)	Gas Detector	Yes
SCBA Quantity	2 w/ Spare Bottle	LEL Monitor	Yes
Self Retracting Lifeline (qty)	2	Crown Saver	Yes
		Pipe Ram Saver	Yes

# **MOBILE DOGHOUSE**

Total Tank Volume (bbl)

Generator Sets	Isuzu	Prime Rating (hp)	53.6
Change Room Size	15' x 9'-8"	Bathroom Facilities	Yes

Generator House Size 15' x 9'-8"

# **MOBILE PUMP & TANK (OPTIONAL EQUIPMENT)**

Truck MFG & Model	Freightliner 2012	Mud Pump Drive	Detroit DD13
Pump MFG & Model	GD TEE 4 x 5	Pump Drive Rating (hp)	410
Pump Rated Power (hp)	165	Pump Pressure (psi)	5,000
Pump Stroke Length	5"	Centrifugal Pump Size	4" x 3"
Manifold Valve Quantity	7	Transmission	Allison 4500 RDS
Manifold Rating (psi)	5,000	# of Tank Compartments	2

Line Pipe Rating (psi)

5,000

# **MISCELLANEOUS EQUIPMENT (OPTIONAL)**

200

Low Lying Slips Type	Bosch	Low Lying Slips Size	As Required
Personal H <sub>2</sub> S Monitor	As Required	NORM Radiation Monitor	As Required
Drill Out Head	As Required	Pipe Trailer	As Required
Skid Boiler (hp)	80	Mud Can	As Required

Standard specifications represent the typical rig configuration, but could be subject to slight modifications from time to time due to customer requirements.