

## **EAGLE** RIG 2 - INTERNALLY GUYED SINGLE

WELL SERVICING Max Depth Capacity: 9,150'

Class II

🐺 A Western Co.

MAST			
Mast Type	Stiff Single	Drill Line Size	1"
Mast MFG	BW Rig	Number of Lines	4
Static Hook Load (lb)	140,000	3:1 Capacity (lb)	125,000
Mast Clear Height	70'	2:1 Capacity (lb)	188,000
Racking Cap. (3-1/2")	6,890'	Sandline Size	9/16" (9,840' Max)
Racking Cap. (2-7/8")	8,200'	Racking Cap. (2-3/8")	9,150'
Drill Line API Specifica	ation for EIPS 6 x 26 is:		
3 : 1 Safety factor drill	ing; 2 : 1 Safety factor runn	ing casing or stuck pipe.	
INTERNAL GUYED CO	MPONENTS		
Rig Beam MFG	Mainland	Geronimo Plate MFG	BW Rig
Outriggers MFG	BW Rig		Ū
	-		
CARRIER Carrier MFG	Mainland	Drawworks Drive	CAT 11
Drawworks Model	Mainland M40	Drive Rating (hp)	325
Rated Power (hp)	400	Transmission	Allison 750
Main Drum Brake Size	40" x 10"	Sandline Drum Brake Size	40" x 10"
OVERHEAD EQUIPME	NT		
Block Type	McKissick 75T	Block Capacity (ton)	75
Bails Type	Tool Pusher 150T	Bail Capacity (ton)	125
Rod Hook Type	Trico 25T	Rod Hook Capacity (ton)	25
Tbg Elevator Type	Diehl / Gearench / AOT	Tbg Elevator Size	2-3/8" to 3-1/2"
Rod Elevator Type	O'Bannon / Trico / Neilson	Rod Elevator Size	5/8" to 1"
HANDLING EQUIPME	NT		
Tbg Tongs Type	Gill 58-93	Tbg Tongs Size	2-3/8" to 3-1/2"
Rod Tongs Type	Oil Country Mark 4	Rod Tongs Size	3/4" to 1"
Rod Backoff Tool Type	Oil Country	Rod Backoff Tool Size	3/4" to 1"
Air Slips Type	С		
BOPs (NACE)			
Double Gate MFG	WSI Duke	Pressure Rating & Size	3,000 psi, 7-1/16"
Kill Spool Pressure Rating & Size		3,000 psi, 7-1/16" c/w 2" Outlet and Valve	
Safety Valve Pressure Rating & Size		5,000 psi, 2-7/8"	
Hydraulic Regan Pressure Rating & Size		3,000 psi, 3" (Type - K)	
ACCUMULATOR			
Class II			
Accumulator MFG	Control Technology	Max Operating Pressure (pai)	3 000
Accumulator Vol. (US g	Control Technology al) 20	Max Operating Pressure (psi) # of Stations	3,000 2
Accumulator vol. (05 g	aij 20		۷.



## ...

SAFETY EQUIPMENT			
Fire Extinguisher Size (qty)	30 lb (4)	Gas Detector	Yes
SCBA Quantity	2 w/ Spare Bottle	LEL Monitor	Yes
Self Retracting Lifeline (qty)	2	Crown Saver	Yes
		Pipe Ram Saver	Yes
MOBILE DOGHOUSE			
Generator Sets	Isuzu	Prime Rating (hp)	53.6
Change Room Size	15' x 9'-8"	Bathroom Facilities	Yes
Generator House Size	15' x 9'-8"		

## **MOBILE PUMP & TANK (OPTIONAL EQUIPMENT)**

Truck MFG & Model	Freightliner 2012	Mud Pump Drive	Detroit DD13
Pump MFG & Model	GD TEE 4 x 5	Pump Drive Rating (hp)	410
Pump Rated Power (hp)	165	Pump Pressure (psi)	5,000
Pump Stroke Length	5"	Centrifugal Pump Size	4" x 3"
Manifold Valve Quantity	7	Transmission	Allison 4500 RDS
Manifold Rating (psi)	5,000	# of Tank Compartments	2
Total Tank Volume (bbl)	200	Line Pipe Rating (psi)	5,000

## **MISCELLANEOUS EQUIPMENT (OPTIONAL)**

Low Lying Slips Type	Bosch	Low Lying Slips Size	As Required
Personal H <sub>2</sub> S Monitor	As Required	NORM Radiation Monitor	As Required
Drill Out Head	As Required	Pipe Trailer	As Required
Skid Boiler (hp)	80	Mud Can	As Required

Standard specifications represent the typical rig configuration, but could be subject to slight modifications from time to time due to customer requirements.