



# RIG 5 - INTERNALLY GUYED SINGLE

Max Depth Capacity: 9,150'

Class II

## MAST

Mast Type	<i>Stiff Single</i>	Drill Line Size	1"
Mast MFG	<i>CARE Industries</i>	Number of Lines	4
Static Hook Load (lb)	<i>150,000</i>	3:1 Capacity (lb)	<i>125,000</i>
Mast Clear Height	<i>72'</i>	2:1 Capacity (lb)	<i>188,000</i>
Racking Cap. (3-1/2")	<i>6,890'</i>	Sandline Size	<i>9/16" (9,840' Max)</i>
Racking Cap. (2-7/8")	<i>8,200'</i>	Racking Cap. (2-3/8")	<i>9,150'</i>

### Drill Line API Specification for EIPS 6 x 26 is:

**3 : 1 Safety factor drilling; 2 : 1 Safety factor running casing or stuck pipe.**

## INTERNAL GUYED COMPONENTS

Rig Beam MFG	<i>CARE Industries</i>	Geronimo Plate MFG	<i>CARE Industries</i>
Turnbuckles MFG	<i>CARE Industries</i>		

## CARRIER

Carrier MFG	<i>Skytop</i>	Drawworks Drive	<i>CAT C10</i>
Drawworks Model	<i>Skytop 42X10</i>	Drive Rating (hp)	<i>365</i>
Rated Power (hp)	<i>400</i>	Transmission	<i>Allison 750</i>
Main Drum Brake Size	<i>42" x 10"</i>	Sandline Drum Brake Size	<i>38" x 8"</i>

## OVERHEAD EQUIPMENT

Block Type	<i>McKissick 75T</i>	Block Capacity (ton)	<i>75</i>
Bails Type	<i>King Oil Tools 150T</i>	Bail Capacity (ton)	<i>150</i>
Rod Hook Type	<i>IR RH-25</i>	Rod Hook Capacity (ton)	<i>25</i>
Tbg Elevator Type	<i>AOT</i>	Tbg Elevator Size	<i>2-7/8" to 3-1/2"</i>
Rod Elevator Type	<i>O'Bannon/Oil Country/Trico</i>	Rod Elevator Size	<i>3/4" to 1-1/4"</i>

## HANDLING EQUIPMENT

Tbg Tongs Type	<i>Gill 58-93</i>	Tbg Tongs Size	<i>2-3/8" to 4-1/2"</i>
Rod Tongs Type	<i>Gill 300</i>	Rod Tongs Size	<i>3/4" to 1"</i>
Rod Backoff Tool Type	<i>Guiberson</i>	Rod Backoff Tool Size	<i>3/4" to 1"</i>
X-Celerator Type	<i>C-Tech X-300</i>	X-Celerator Capacity (lb)	<i>16,000</i>
Air Slips Type	<i>C</i>		

## BOPs (NACE)

Double Gate MFG	<i>Control Technology</i>	Pressure Rating & Size	<i>5,000 psi, 7-1/16"</i>
Kill Spool Pressure Rating & Size			<i>5,000 psi, 7-1/16" c/w 2" Outlet and Valve</i>
Safety Valve Pressure Rating & Size			<i>5,000 psi, 2-7/8"</i>
Hydraulic Regan Pressure Rating & Size			<i>3,000 psi, 3" (Type - K)</i>

## ACCUMULATOR

<b>Class II</b>			
Accumulator MFG	<i>Control Technology</i>	Max Operating Pressure (psi)	<i>3,000</i>
Accumulator Vol. (US gal)	<i>20</i>	# of Stations	<i>2</i>



**Sales and Marketing**  
**Eagle Well Servicing**

**Tel: 1-877-346-9710 Email: sales@eaglerigs.com**

---

**SAFETY EQUIPMENT**

Fire Extinguisher Size (qty)	30 lb (4)	Gas Detector	Yes
SCBA Quantity	2 w/ Spare Bottle	LEL Monitor	Yes
Self Retracting Lifeline (qty)	2	Crown Saver	Yes
		Pipe Ram Saver	Yes

**MOBILE DOGHOUSE**

Generator Sets	Yanmar	Prime Rating (hp)	67
Change Room Size	15' x 9'-8"	Bathroom Facilities	Yes
Generator House Size	15' x 9'-8"	Wi-Fi Hotspot Booster	Yes

**EQUIPMENT TRUCK WITH PICKER**

Crane MFG & Model	Maxilift 300.3H	Crane Lifting Capacity (lb)	4,510
Truck MFG & Model	Freightliner M2		

**MOBILE PUMP & TANK (OPTIONAL EQUIPMENT)**

Truck MFG & Model	International 2014	Mud Pump Drive	MaxxForce 13
Pump MFG & Model	SJ Petro 300	Pump Drive Rating (hp)	410
Pump Rated Power (hp)	350	Pump Pressure (psi)	5,000
Pump Stroke Length	5"	Bowie Pump Size	3"
Manifold Valve Quantity	7	Transmission	Allison 4500 RDS
Manifold Rating (psi)	5,000	# of Tank Compartments	2
Total Tank Volume (bbl)	200	Line Pipe Rating (psi)	5,000

**MISCELLANEOUS EQUIPMENT (OPTIONAL)**

Low Lying Slips Type	Bosch	Low Lying Slips Size	As Required
Personal H <sub>2</sub> S Monitor	As Required	NORM Radiation Monitor	As Required
Drill Out Head	As Required	Pipe Trailer	As Required
Skid Boiler (hp)	80	Mud Can	As Required

*Standard specifications represent the typical rig configuration, but could be subject to slight modifications from time to time due to customer requirements.*