

RIG 9 - INTERNALLY GUYED SINGLE

Max Depth Capacity: 9,150'

Class II

MAST

Mast Type	<i>Stiff Single</i>	Drill Line Size	1"
Mast MFG	<i>CARE Industries</i>	Number of Lines	4
Static Hook Load (lb)	150,000	3:1 Capacity (lb)	125,000
Mast Clear Height	72'	2:1 Capacity (lb)	188,000
Racking Cap. (3-1/2")	6,890'	Sandline Size	9/16" (9,840' Max)
Racking Cap. (2-7/8")	8,200'	Racking Cap. (2-3/8")	9,150'

Drill Line API Specification for EIPS 6 x 26 is:

3 : 1 Safety factor drilling; 2 : 1 Safety factor running casing or stuck pipe.

INTERNAL GUYED COMPONENTS

Rig Beam MFG	<i>CARE Industries</i>	Geronimo Plate MFG	<i>CARE Industries</i>
Turnbuckles MFG	<i>CARE Industries</i>		

CARRIER

Carrier MFG	<i>Skytop</i>	Drawworks Drive	<i>CAT C10</i>
Drawworks Model	<i>Skytop 42X10</i>	Drive Rating (hp)	365
Rated Power (hp)	400	Transmission	<i>Allison 750</i>
Main Drum Brake Size	42" x 10"	Sandline Drum Brake Size	38" x 8"

OVERHEAD EQUIPMENT

Block Type	<i>McKissick 75T</i>	Block Capacity (ton)	75
Bails Type	<i>Cavins 150T</i>	Bail Capacity (ton)	150
Rod Hook Type	<i>O'Bannon 25T</i>	Rod Hook Capacity (ton)	25
Tbg Elevator Type	<i>Diehl / AOT</i>	Tbg Elevator Size	2-7/8" to 3-1/2"
Rod Elevator Type	<i>Trico Plate Type</i>	Rod Elevator Size	3/4" to 1-1/4"

HANDLING EQUIPMENT

Tbg Tongs Type	<i>Gill 58-93</i>	Tbg Tongs Size	2-3/8" to 4-1/2"
Rod Tongs Type	<i>Gill 300</i>	Rod Tongs Size	3/4" to 1"
Rod Backoff Tool Type	<i>Guiberson</i>	Rod Backoff Tool Size	3/4" to 1"
X-Celerator Type	<i>C-Tech X-300</i>	X-Celerator Capacity (lb)	16,000
Air Slips Type	C		

BOPs (NACE)

Double Gate MFG	<i>Unity Rig</i>	Pressure Rating & Size	3,000 psi, 7-1/16"
Kill Spool Pressure Rating & Size			3,000 psi, 7-1/16" c/w 2" Outlet and Valve
Safety Valve Pressure Rating & Size			5,000 psi, 2-7/8" & 3-1/2"
Hydraulic Regan Pressure Rating & Size			3,000 psi, 3" (Type - K)

ACCUMULATOR

Class II			
Accumulator MFG	<i>Control Technology</i>	Max Operating Pressure (psi)	3,000
Accumulator Vol. (US gal)	20	# of Stations	2

SAFETY EQUIPMENT

Fire Extinguisher Size (qty)	30 lb (4)	Gas Detector	Yes
SCBA Quantity	2 w/ Spare Bottle	LEL Monitor	Yes
Self Retracting Lifeline (qty)	2	Crown Saver	Yes
		Pipe Ram Saver	Yes

MOBILE DOGHOUSE

Generator Sets	Yanmar	Prime Rating (hp)	53.6
Change Room Size	15' x 9'-8"	Bathroom Facilities	Yes
Generator House Size	15' x 9'-8"	Wi-Fi Hotspot Booster	Yes

EQUIPMENT TRUCK WITH PICKER

Crane MFG & Model	Maxilift ML300.3	Crane Lifting Capacity (lb)	4,510
Truck MFG & Model	Freightliner M2		

MOBILE PUMP & TANK (OPTIONAL EQUIPMENT)

Truck MFG & Model	Freightliner 2005	Mud Pump Drive	CAT C7
Pump MFG & Model	GD TEE 4 x 5	Pump Drive Rating (hp)	300
Pump Rated Power (hp)	165	Pump Pressure (psi)	5,000
Pump Stroke Length	5"	Centrifugal Pump Size	4" x 3"
Manifold Valve Quantity	7	Transmission	Allison 3000 RDS
Manifold Rating (psi)	5,000	# of Tank Compartments	2
Total Tank Volume (bbl)	200	Line Pipe Rating (psi)	5,000

MISCELLANEOUS EQUIPMENT (OPTIONAL)

Low Lying Slips Type	Bosch	Low Lying Slips Size (mm)	As Required
Personal H ₂ S Monitor	As Required	NORM Radiation Monitor	As Required
Drill Out Head (mm)	As Required	Pipe Trailer	As Required
Skid Boiler (kW)	60	Mud Can	As Required

Standard specifications represent the typical rig configuration, but could be subject to slight modifications from time to time due to customer requirements.