



**MAST**

Mast Type	<i>Stiff Single</i>	Drill Line Size (mm)	25.4
Mast MFG	<i>CARE Industries</i>	Number of Lines	4
Static Hook Load (daN)	66,700	3:1 Capacity (daN)	55,800
Mast Clear Height (m)	21.9	2:1 Capacity (daN)	83,600
Racking Cap.-88.9mm (m)	2,100	Sandline Size (mm)	14.3 (3,000 m Max)
Racking Cap.-73.0mm (m)	2,500	Racking Cap.-60.3mm (m)	2,800

**Drill Line API Specification for EIPS 6 x 26 is:**

**3 : 1 Safety factor drilling; 2 : 1 Safety factor running casing or stuck pipe.**

**INTERNAL GUYED COMPONENTS**

Rig Beam MFG	<i>CARE Industries</i>	Geronimo Plate MFG	<i>CARE Industries</i>
Turnbuckles MFG	<i>CARE Industries</i>		

**CARRIER**

Carrier MFG	<i>Skytop</i>	Drawworks Drive	<i>CAT C10</i>
Drawworks Model	<i>Skytop 42X10</i>	Drive Rating (kW)	272
Rated Power (kW)	300	Transmission	<i>Allison 750</i>
Main Drum Brake Size (mm)	1,067 x 254	Sandline Drum Brake Size (mm)	965 x 203

**OVERHEAD EQUIPMENT**

Block Type	<i>McKissick 75T</i>	Block Capacity (daN)	66,700
Bails Type	<i>King Oil Tools 150T</i>	Bail Capacity (daN)	133,400
Rod Hook Type	<i>O'Bannon 25T</i>	Rod Hook Capacity (daN)	22,200
Tbg Elevator Type	<i>AOT/Oil Country/Gearench</i>	Tbg Elevator Size (mm)	60.3 to 88.9
Rod Elevator Type	<i>O'Bannon / Trico</i>	Rod Elevator Size (mm)	15.8 To 25.4

**HANDLING EQUIPMENT**

Tbg Tongs Type	<i>Gill 58-93</i>	Tbg Tongs Size (mm)	60.3 to 88.9
Rod Tongs Type	<i>Gill 300</i>	Rod Tongs Size (mm)	19.1 to 25.4
Rod Backoff Tool Type	<i>Oil Country</i>	Rod Backoff Tool Size (mm)	19.1 to 25.4
Air Slips Type	<i>C</i>		

**BOPs (NACE)**

Double Gate MFG	<i>Boss</i>	Pressure Rating & Size	34,500 kPa, 179 mm
Kill Spool Pressure Rating & Size			34,500 kPa, 179 mm c/w 50.8 mm Outlet and Valve
Safety Valve Pressure Rating & Size			34,500 kPa, 73 mm
Hydraulic Regan Pressure Rating & Size			21,000 kPa, 76.2 mm (Type - K)

**ACCUMULATOR**

**Class II**

Accumulator MFG	<i>Control Technology</i>	Max Operating Pressure (kPa)	21,000
Accumulator Vol. (l)	76	# of Stations	2

### SAFETY EQUIPMENT

Fire Extinguisher Size (qty)	13.6 kg (7)	Gas Detector	Yes
SCBA Quantity	2 w/ Spare Bottle	LEL Monitor	Yes
Self Retracting Lifeline (qty)	2	Crown Saver	Yes
		Pipe Ram Saver	Yes

### MOBILE DOGHOUSE

Generator Sets	Isuzu	Prime Rating (kW)	40
Change Room Size (m)	4.57 x 2.95	Bathroom Facilities	Yes
Generator House Size (m)	4.57 x 2.95	Wi-Fi Hotspot Booster	Yes

### MOBILE PUMP & TANK (OPTIONAL EQUIPMENT)

Truck MFG & Model	Freightliner 2005	Mud Pump Drive	CAT C7
Pump MFG & Model	GD TEE 4 x 5	Pump Drive Rating (kW)	224
Pump Rated Power (kW)	123	Pump Pressure (kPa)	34,500
Pump Stroke Length (mm)	127	Centrifugal Pump Size (mm)	101 x 76
Manifold Valve Quantity	7	Transmission	Allison 3000 RDS
Manifold Rating (kPa)	34,500	# of Tank Compartments	2
Total Tank Volume (m <sup>3</sup> )	32	Line Pipe Rating (kPa)	34,500

### MISCELLANEOUS EQUIPMENT (OPTIONAL)

Low Lying Slips Type	Bosch	Low Lying Slips Size (mm)	As Required
Personal H <sub>2</sub> S Monitor	As Required	NORM Radiation Monitor	As Required
Drill Out Head (mm)	As Required	Pipe Trailer	As Required
Skid Boiler (kW)	60	Mud Can	As Required

Standard specifications represent the typical rig configuration, but could be subject to slight modifications from time to time due to customer requirements.