

# RIG 12 - INTERNALLY GUYED SINGLE

Max Depth Capacity: 9,150'

Class II

## MAST

|                       |                        |                       |                    |
|-----------------------|------------------------|-----------------------|--------------------|
| Mast Type             | <i>Stiff Single</i>    | Drill Line Size       | 1"                 |
| Mast MFG              | <i>CARE Industries</i> | Number of Lines       | 4                  |
| Static Hook Load (lb) | 150,000                | 3:1 Capacity (lb)     | 125,000            |
| Mast Clear Height     | 72'                    | 2:1 Capacity (lb)     | 188,000            |
| Racking Cap. (3-1/2") | 6,890'                 | Sandline Size         | 9/16" (9,840' Max) |
| Racking Cap. (2-7/8") | 8,200'                 | Racking Cap. (2-3/8") | 9,150'             |

**Drill Line API Specification for EIPS 6 x 26 is:**

**3 : 1 Safety factor drilling; 2 : 1 Safety factor running casing or stuck pipe.**

## INTERNAL GUYED COMPONENTS

|                 |                        |                    |                        |
|-----------------|------------------------|--------------------|------------------------|
| Rig Beam MFG    | <i>CARE Industries</i> | Geronimo Plate MFG | <i>CARE Industries</i> |
| Turnbuckles MFG | <i>CARE Industries</i> |                    |                        |

## CARRIER

|                      |                     |                          |                    |
|----------------------|---------------------|--------------------------|--------------------|
| Carrier MFG          | <i>Skytop</i>       | Drawworks Drive          | <i>CAT C10</i>     |
| Drawworks Model      | <i>Skytop 42X10</i> | Drive Rating (hp)        | 365                |
| Rated Power (hp)     | 400                 | Transmission             | <i>Allison 750</i> |
| Main Drum Brake Size | 42" x 10"           | Sandline Drum Brake Size | 38" x 8"           |

## OVERHEAD EQUIPMENT

|                   |                                   |                         |                  |
|-------------------|-----------------------------------|-------------------------|------------------|
| Block Type        | <i>McKissick 75T</i>              | Block Capacity (ton)    | 75               |
| Bails Type        | 150T                              | Bail Capacity (ton)     | 150              |
| Rod Hook Type     | <i>BJ 20T</i>                     | Rod Hook Capacity (ton) | 20               |
| Tbg Elevator Type | <i>Diehl / AOT</i>                | Tbg Elevator Size       | 2-3/8" to 2-7/8" |
| Rod Elevator Type | <i>Trico / Monarch / O'Bannon</i> | Rod Elevator Size       | 3/4" to 1"       |

## HANDLING EQUIPMENT

|                       |                           |                           |                  |
|-----------------------|---------------------------|---------------------------|------------------|
| Tbg Tongs Type        | <i>Gill 58-93</i>         | Tbg Tongs Size            | 2-3/8" to 3-1/2" |
| Rod Tongs Type        | <i>Gill 300</i>           | Rod Tongs Size            | 3/4" to 1"       |
| Rod Backoff Tool Type | <i>Metaltek Machining</i> | Rod Backoff Tool Size     | 3/4" to 1"       |
| X-Celerator           | <i>C-Tech X-300</i>       | X-Celerator Capacity (lb) | 16,000           |
| Air Slips Type        | C                         |                           |                  |

## BOPs (NACE)

|  |            |                        |  |
|--|------------|------------------------|--|
| Double Gate MFG                        | <i>IEI</i> | Pressure Rating & Size | 5,000 psi, 7-1/16"                         |
| Kill Spool Pressure Rating & Size      |            |                        | 3,000 psi, 7-1/16" c/w 2" Outlet and Valve |
| Safety Valve Pressure Rating & Size    |            |                        | 5,000 psi, 2-7/8" & 3-1/2"                 |
| Hydraulic Regan Pressure Rating & Size |            |                        | 3,000 psi, 3" (Type - K)                   |

## ACCUMULATOR

|                           |                           |                              |       |
|---------------------------|---------------------------|------------------------------|-------|
| <b>Class II</b>           |                           |                              |       |
| Accumulator MFG           | <i>Control Technology</i> | Max Operating Pressure (psi) | 3,000 |
| Accumulator Vol. (US gal) | 20                        | # of Stations                | 2     |



**Sales and Marketing**  
**Eagle Well Servicing**  
**Tel: 1-877-346-9710    Email: sales@eaglerigs.com**

---

**SAFETY EQUIPMENT**

|                                |                          |                |     |
|--------------------------------|--------------------------|----------------|-----|
| Fire Extinguisher Size (qty)   | <i>30 lb (4)</i>         | Gas Detector   | Yes |
| SCBA Quantity                  | <i>2 w/ Spare Bottle</i> | LEL Monitor    | Yes |
| Self Retracting Lifeline (qty) | <i>2</i>                 | Crown Saver    | Yes |
|                                |                          | Pipe Ram Saver | Yes |

**MOBILE DOGHOUSE**

|                      |                    |                       |             |
|----------------------|--------------------|-----------------------|-------------|
| Generator Sets       | <i>Isuzu</i>       | Prime Rating (hp)     | <i>53.6</i> |
| Change Room Size     | <i>15' x 9'-8"</i> | Bathroom Facilities   | Yes         |
| Generator House Size | <i>15' x 9'-8"</i> | Wi-Fi Hotspot Booster | Yes         |

**EQUIPMENT TRUCK WITH PICKER**

|                   |                        |                             |               |
|-------------------|------------------------|-----------------------------|---------------|
| Crane MFG & Model | <i>Fassi F150C</i>     | Crane Lifting Capacity (lb) | <i>13,360</i> |
| Truck MFG & Model | <i>Freightliner M2</i> |                             |               |

**MISCELLANEOUS EQUIPMENT (OPTIONAL)**

|                                   |                    |                        |                    |
|-----------------------------------|--------------------|------------------------|--------------------|
| Low Lying Slips Type              | <i>Bosch</i>       | Low Lying Slips Size   | <i>As Required</i> |
| Personal H <sub>2</sub> S Monitor | <i>As Required</i> | NORM Radiation Monitor | <i>As Required</i> |
| Drill Out Head                    | <i>As Required</i> | Pipe Trailer           | <i>As Required</i> |
| Mobile Pump & Tank                | <i>As Required</i> | Mud Can                | <i>As Required</i> |
| Skid Boiler (hp)                  | <i>80</i>          |                        |                    |

*Standard specifications represent the typical rig configuration, but could be subject to slight modifications from time to time due to customer requirements.*