



**O'CHIESE EAGLE RIG 2**  
**- INTERNALLY GUYED DOUBLE**  
**Max Depth Capacity: 12,450' Class II / III**



**MAST**

Mast Type	<i>Telescopic Double</i>	Drill Line Size	1"
Mast MFG	<i>CBI</i>	Number of Lines	6
SHL - Externally Guyed (lb)	<i>200,000</i>	3:1 Capacity (lb)	<i>180,500</i>
Mast Clear Height	<i>100'-10"</i>	2:1 Capacity (lb)	<i>270,700</i>
Racking Cap. (3-1/2")	<i>12,450'</i>	Sandline Size	<i>1/2" (13,780' Max)</i>

**Drill Line API Specification for EIPS 6 x 26 is:**

**3 : 1 Safety factor drilling; 2 : 1 Safety factor running casing or stuck pipe.**

**INTERNAL GUYED COMPONENTS**

Rig Beam MFG	<i>CBI</i>	Geronimo Plate MFG	<i>CBI</i>
Turnbuckles MFG	<i>CBI</i>		

**CARRIER**

Carrier MFG	<i>CBI</i>	Drawworks Drive	<i>CAT C11</i>
Drawworks Model	<i>ALCO 42X20</i>	Drive Rating (hp)	<i>350</i>
Rated Power (hp)	<i>450</i>	Transmission	<i>CAT TH31</i>
Main Drum Brake Size	<i>42" x 10"</i>	Sandline Drum Brake Size	<i>38" x 8"</i>
Auxiliary Brake	<i>Kobelt 40" Disc</i>		

**OVERHEAD EQUIPMENT**

Block Type	<i>McKissick 100T</i>	Block Capacity (ton)	<i>100</i>
Bails Type	<i>BVM 150T</i>	Bail Capacity (ton)	<i>150</i>
Rod Hook Type	<i>Trico 25T</i>	Rod Hook Capacity (ton)	<i>25</i>
Tbg Elevator Type	<i>Oil Country / Gearench</i>	Tbg Elevator Size	<i>2-3/8" to 3-1/2"</i>
Rod Elevator Type	<i>Trico 25T</i>	Rod Elevator Size	<i>3/4" to 1"</i>

**HANDLING EQUIPMENT**

Tbg Tongs Type	<i>Oil Country 58-93</i>	Tbg Tongs Size	<i>2-3/8" to 3-1/2"</i>
Air Slips Type	<i>C</i>		

**BOPs (NACE)**

Annular MFG	<i>IEI</i>	Pressure Rating & Size	<i>5,000 psi, 7-1/16"</i>
Double Gate MFG	<i>IEI</i>	Pressure Rating & Size	<i>5,000 psi, 7-1/16"</i>
Kill Spool Pressure Rating & Size			<i>5,000 psi, 7-1/16" c/w 2" Outlet and Valve</i>
Safety Valve Pressure Rating & Size			<i>5,000 psi, 2-7/8" &amp; 3-1/2"</i>
Hydraulic Regan Pressure Rating & Size			<i>3,000 psi, 3" (Type - K)</i>

**ACCUMULATOR**

**Class II**

Accumulator MFG	<i>Control Technology</i>	Max Operating Pressure (psi)	<i>3,000</i>
Accumulator Vol. (US gal)	<i>20</i>	# of Stations	<i>2</i>

**Class III**

Accumulator MFG	<i>Control Technology</i>	Max Operating Pressure (psi)	<i>3,000</i>
Accumulator Vol. (US gal)	<i>40</i>	# of Stations	<i>3</i>



**Sales and Marketing  
Eagle Well Servicing**

**Tel: 1-877-346-9710**

**Email: [sales@eaglerigs.com](mailto:sales@eaglerigs.com)**

---

**SAFETY EQUIPMENT**

Fire Extinguisher Size (qty)	30 lb (4)	Gas Detector	Yes
SCBA Quantity	2 w/ Spare Bottle	LEL Monitor	Yes
Self Retracting Lifeline (qty)	2	Crown Saver	Yes
		Pipe Ram Saver	Yes

**MOBILE DOGHOUSE**

Generator Sets	Isuzu	Prime Rating (hp)	53.6
Change Room Size	15' x 9'-4"	Bathroom Facilities	Yes
Generator House Size	15' x 9'-4"		

**MOBILE PUMP & TANK (OPTIONAL EQUIPMENT)**

Truck MFG	International 2012	Mud Pump Drive	MaxxForce 11
Pump MFG & Model	SJ Petro 300	Pump Drive Rating (hp)	370
Pump Rated Power (hp)	350	Pump Pressure (psi)	5,000
Pump Stroke Length	5"	Bowie Pump Size	3"
Manifold Valve Quantity	7	Transmission	Allison 4500 RDS
Manifold Rating (psi)	5,000	# of Tank Compartments	2
Total Tank Volume (bbl)	200	Line Pipe Rating (psi)	5,000

**MISCELLANEOUS EQUIPMENT (OPTIONAL)**

Rod Tongs Type	M50	Rod Tongs Size	As Required
Rod Backoff Tool Type	Oil Country	Rod Backoff Tool Size	As Required
Low Lying Slips Type	Bosch	Low Lying Slips Size	As Required
Personal H <sub>2</sub> S Monitor	As Required	NORM Radiation Monitor	As Required
Drill Out Head	As Required	Mud Can	As Required
Skid Boiler (hp)	80		

*Standard specifications represent the typical rig configuration, but could be subject to slight modifications from time to time due to customer requirements.*

---